

Etanorm SYT		50 Hz	60 Hz
Flow	Q [m ³ /h]	≤ 625	≤ 754
Løftehøjde	H [m]	≤ 102	≤ 100
Temperatur Termisk olie	T [°C]	≤ 350	≤ 350
Temperatur hedt vand		≤ 180	≤ 180
Tryk	p [bar]	≤ 16	≤ 16

Etabloc SYT		50 Hz	60 Hz
Flow	Q [m ³ /h]	≤ 280	≤ 337
Løftehøjde	H [m]	≤ 68	≤ 99
Temperatur Termisk olie	T [°C]	≤ 350	≤ 350
Temperatur hedt vand		≤ 180	≤ 180
Tryk	p [bar]	≤ 16	≤ 16

Etaline SYT (vertikal)		50 Hz	60 Hz
Flow	Q [m ³ /h]	≤ 316	≤ 228
Løftehøjde	H [m]	≤ 69	≤ 101
Temperatur Termisk olie	T [°C]	≤ 350	≤ 350
Temperatur hedt vand		≤ 180	≤ 180
Tryk	p [bar]	≤ 16	≤ 16

HPK		Maks. værdier
Flow	Q [m ³ /h]	≤ 4.800
Løftehøjde	H [m]	≤ 275
Temperatur Termisk olie	T [°C]	≤ 400
Temperatur hedt vand		≤ 240
Tryk	p [bar]	≤ 40